## **Parts List Middex Tool Monitors**



**Caring Beyond Our Products** 

| System       | Part                                       | Part#  | Comment  |
|--------------|--|--------|--|
| WK-1T &      | Controller 24/110V                         | 9002   | only repairs made, replaced with WK2   |
| WK-4T        | Controller 24V                             | 9006   | only repairs made, replaced with WK2   |
|              | Sensor WKR22-45                            | 9020   | dia. 22mm sensor, 45° right turning  |
|              | Sensor WKR22-60                            | 9021   | dia. 22mm sensor, 60° right turning  |
|              | Sensor WKR22-90                            | 9022   | dia. 22mm sensor, 90° right turning  |
|              | Sensor WKR22-120                           | 9023   | dia. 22mm sensor, 120° right turning   |
|              | Sensor WKR22-180                           | 9024   | dia. 22mm sensor, 180° right turning   |
|              | Sensor WKL22-45                            | 9030   | dia. 22mm sensor, 45° left turning   |
|              | Sensor WKL22-60                            | 9031   | dia. 22mm sensor, 60° left turning   |
|              | Sensor WKL22-90                            | 9032   | dia. 22mm sensor, 90° left turning   |
|              | Sensor WKL22-120                           | 9033   | dia. 22mm sensor, 120° left turning  |
|              | Sensor WKL22-180                           | 9034   | dia. 22mm sensor, 180° left turning  |
| Cables       | 3m (9') 90° connector                      | 9026   | plug on sensor end, open leads on other  |
|              | 5m (16') 90° connector                     | 9027   | plug on sensor end, open leads on other  |
|              | 10m (30') 90° connector                    | 9028   | plug on sensor end, open leads on other  |
|              | 20m (60') 90° connector                    | 9038   | plug on sensor end, open leads on other  |
|              | 3m (9') straight connector                 | 9035   | plug on sensor end, open leads on other  |
|              | 5m (16') straight connector                | 9036   | plug on sensor end, open leads on other  |
|              | 10m (30') straight connector               | 9037   | plug on sensor end, open leads on other  |
| Probe Assen  | nblies see WK1 section below               |        |  |
| <br>WK1      | Controller 24V/24Vdc                       | 9011   | 24Vdc PLC cards, replaced with WK2   |
| WK1A         | Controller 24V/115Vac                      | 9012   | cancelled, serviced only, replaced with WK2  |
| WINIA        |  |        |  |
|              | Sensor WKLR22-45                           | 9050   | dia. 22mm sensor, 45° left/right turning   |
|              | Sensor WKLR22-60                           | 9051   | dia. 22mm sensor, 60° left/right turning   |
|              | Sensor WKLR22-90                           | 9052   | dia. 22mm sensor, 90° left/right turning   |
|              | Sensor WKLR22-120                          | 9053   | dia. 22mm sensor, 120° left/right turning  |
|              | Sensor WKLR22-180                          | 9054   | dia. 22mm sensor, 180° left/right turning  |
|              | Sensor WKLR32-45                           | 9060   | dia. 32mm sensor, 45° left/right turning   |
|              | Sensor WKLR32-60                           | 9061   | dia. 32mm sensor, 60° left/right turning   |
|              | Sensor WKLR32-90                           | 9062   | dia. 32mm sensor, 90° left/right turning   |
|              | Sensor WKLR32-120                          | 9063   | dia. 32mm sensor, 120° left/right turning  |
|              | Sensor WKLR32-180                          | 9064   | dia. 32mm sensor, 180° left/right turning  |
|              |  |        |  |
| Cables       | 3m (9') 90° connector                      | 9026   | plug on sensor end, open leads on other  |
|              | 5m (16') 90° connector                     | 9027   | plug on sensor end, open leads on other  |
|              | 10m (30') 90° connector                    | 9028   | plug on sensor end, open leads on other  |
|              | 20m (60') 90° connector                    | 9038   | plug on sensor end, open leads on other  |
|              | 3m `(9') straight connector                | 9035   | plug on sensor end, open leads on other  |
|              | 5m (16') straight connector                | 9036   | plug on sensor end, open leads on other  |
|              | 10m (30') straight connector               | 9037   | plug on sensor end, open leads on other  |
|              | , , -                                      |        |  |
| Probe -      | 100mm (4") steel, brass end                | 9055   | dia. 13x13mm probe holder (old #: 9070-B)  |
| Assemblies   | 130mm (5") steel                           | 9071-B | dia. 13x13mm probe holder  |
|              | 150mm (6") steel                           | 9072-B | dia. 13x13mm probe holder  |
|              | 200mm (8") steel                           | 9073-B | dia. 13x13mm probe holder  |
|              | 100mm (4") steel, carbide end              | 9070   | dia. 13x13mm probe holder, wear resistant  |
|              | 130mm (5") steel, carbide end              | 9071-H | dia. 13x13mm probe holder, wear resistant  |
|              | 150mm (6") steel, carbide end              | 9072-H | dia. 13x13mm probe holder, wear resistant  |
| <br>WK2      | Controller 24Vdc                           | 9400   | 24Vdc PLC cards, replacing WK1, WK1T, WK4T   |
|              | Sensor WK2                                 | 9401   | dia. 22mm, 15° to 270° left/right turning, with probe                                      |
|              | Controller 24Vdc                           | 9420   | pnp, npn, latching/non latching, inverting outputs   |
| WK2A         | Controller 24 vac                          |        | replacing WK2, WK2S  |
|              |  | 0.404  |  |
| WK2A<br>WK2S | Controller 24Vdc                           | 9431   | pnp, npn, latching/non-latching, inverting outputs   |
|              | Controller 24Vdc<br>5m (16') 90° connector | 9402   | pnp, npn, latching/non-latching, inverting outputs plug on sensor end, open leads on other |
| WK2S         | Controller 24Vdc                           |        | pnp, npn, latching/non-latching, inverting outputs   |

Toll free:

Phone:

Fax:

(888) ASK CIRO

(828) 345-6030

(828) 345-6013

Web:

www.ciro.com

E-mail: info@ciro.com



## **Caring Beyond Our Products**

| System                | Part   | Part#  | Comment  |
|-----------------------|--|--|--|
| Assemblies            | 160mm (6-1/4") steel, standard   | 9411   | complete probe assembly with shavings deflector  |
| Probe only            | 160mm steel, carbide end<br>200mm steel, carbide end<br>Probe holder only  | 9412<br>9413<br>9410   | cap at end of needle in carbide, wear resistant cap at end of needle in carbide, wear resistant complete holder, without steel probe         |
| WK3                   | Controller WK3A<br>Sensor WK3TA<br>Mounting bracket (BKS1)   | 9450<br>9451<br>9107   | 24 Vdc<br>dia. 32mm, 10° - 270° left/right, without probe<br>threaded M5, see installation manual  |
| Cables                | 5m (9') 90° connector<br>10m (32') 90° connector   | 9455<br>9456   | plug on sensor end, open leads on other plug on sensor end, open leads on other  |
| Probe<br>Assemblies   | 100mm (4") carbon fiber<br>200mm (8") carbon fiber<br>270mm (10.5") carbon fiber   | 9462<br>9463<br>9464   | probe holder and carbon rod<br>probe holder and carbon rod<br>probe holder and carbon rod  |
| WK5                   | Controller WK5<br>Sensor WKT5  | 9550<br>9554   | 24V, pnp, especially for small tools one tool, especially for small tools  |
| Cables                | 5m (9') straight connector 10m (32') straight connector  | 9557<br>9558   | plugs on both ends<br>plugs on both ends   |
| Probe<br>Assembly     | 160mm (6-1/4") carbon, standard  | 9556   | complete probe assembly  |
| BKS1<br>BKS1S         | Controller BKS1<br>Controller BKS1S<br>Sensor BKS1<br>Mounting bracket BKS1  | 9100<br>9109<br>9101<br>9107   | one/two tools<br>one/two tools, replaces BKS1, expanded features<br>dia. 32mm, one/two tools<br>threaded M5, see installation manual         |
| Cables                | 10m (32') straight connector 20m (65') straight connector  | 9118<br>9119   | plugs on one, open leads on other end, BKS1S plugs on one, open leads on other end, BKS1S  |
| Cables                | 5m (16') straight connector<br>10m (32') straight connector<br>20m (65') straight connector  | 9102<br>9103<br>9104   | plugs on both ends, BKS1<br>plugs on both ends, BKS1<br>plugs on both ends, BKS1   |
| Probe -<br>Assemblies | 150mm (6") steel, standard<br>200mm (8") steel<br>150mm (6") steel, carbide end  | 9072-B<br>9073-B<br>9072-H   | dia. 13x13mm probe holder<br>dia. 13x13mm probe holder<br>dia. 13x13mm probe holder, wear resistant  |
| Peripheral -<br>Units | Power supply PS1A<br>Interface RIF1<br>Interface PSIF1A<br>Interface PSIF1A  | 9015<br>9040<br>9045<br>9046   | 110/220V/24Vdc (**WK1, WK2, WK3, WK5, BKS1S) relay only power supply & relay, 110V/24Vdc (**) power supply & relay, 220V/24Vdc (**)          |
| TCS1                  | Controller TCS1 Sensor TCS1 Mounting bracket TCS1 Sensor bar 50mm type 1 Sensor bar 100mm type 1 Sensor bar 50mm type 2 Sensor bar 100mm type 2 Sensor bar 50mm type 3 Sensor bar 100mm type 3 | 9005<br>9025<br>9029<br>9080<br>9081<br>9082<br>9083<br>9084<br>9085 | *** Cancelled, serviced only  ***  ***  ***  ***  ***  ***  ***  |
| Cables                | 3m (9') straight connector<br>5m (16') straight connector<br>10m (32') straight connector  | 9068<br>9069<br>9075   | ***, plug on sensor end, open leads on other<br>***, plug on sensor end, open leads on other<br>***, plug on sensor end, open leads on other |

All text, technical data, measurements and samples were prepared thoroughly. However Middex Electronic and CIRO Products Ltd. cannot be held liable for errors and omissions. Middex Electronic and CIRO Products Ltd. reserve the right to improve or change the design of hard and software and make changes to the technical documentation without further notice.

(888) ASK CIRO

(828) 345-6030

(828) 345-6013

Web:

www.ciro.com

E-mail: info@ciro.com

Toll free:

Phone:

Fax: